



OneScreen Wall

State-of-the-art active bezel video wall



The state-of-the-art,
active bezel video wall of choice for
organizations wanting the highest quality.



OneScreen Wall w2

Display	
Pixel Pitch	0.63mm
Resolution (per panel)	1920x1080
Diagonal Length of Panel	55"
Viewing Angle	178°
Input Ports (on panel)	BNC, DVI, HDMI, RS 232, USB, VGA
Wall Type	TFT-LCD
Bezel Width	0 mm
Active Bezel	Yes
Warranty	3 years
Power Requirements	AC 100-240V, 50/60 Hz
Power Consumption Max (per panel)	≤280W
Colors	16.7M
Contrast	4500 : 1
Brightness	500 cd/m2
Response Time	6 ms
Noise Free Operation	Yes
Environment	Indoor
Operating Temperature	0 - 40° C
Humidity	≤ 90% (No Condensation)
Weight	66 lbs
Dimensions	47.9" x 27.1" x 4.2"

**Specifications are subject to change at any time without notice.
Copyright April 2018. All rights reserved*

LCD Panels

- 0mm active bezel technology for dead bezel sensitive customers
- The most narrow pixel pitch available
- Individual panel and content control
- Seamless and high quality display
- 55" panels that allow a customized video wall

Support and Installation

- Complete turnkey solution
- Durable floor stand included
- Video wall hardware, control system technology and installation from one company
- Free unlimited training and technical support
- 3 year warranty



Premium Quality Tech

Zero millimeter, active bezel seamlessly connecting up to 144 screens at once.



Flexible Design

Custom sizing, front side service, and multiple input sources.



Turnkey Solution

Video wall hardware, control system technology and installation from one company.



Support Centric

Live help, in one click, so your work moves forward now.



CALL US AT 800.992.5279

onescreensolutions.com/ sales@onescreensolutions.com